

Evaluation guideline

for the Kiwa product certificate for Shower heads and hand showers for sanitary tapware



BRL-K658/07 01-02-2012

Preface

This evaluation guideline has been accepted by the board of experts CWK of Kiwa, in which the parties concerned in the sector Drinkingwater appliances are being represented. This Board of Experts also supervises the certification activities and where necessary requires the evaluation guideline to be revised. All references to Board of Experts in this evaluation guideline pertain to the above mentioned Board of Experts.

This evaluation guideline will be used by Kiwa in conjunction with the Kiwa-Regulations for Product Certification. This regulation details the method employed by Kiwa for conducting the necessary investigations prior to issuing the product certificate and the method of external control.

This evaluation guideline is to be assessed by the Board of Experts at least every 5 years, but at the latests before 1 February 2017.

Kiwa N.V. Sir W. Churchill-laan 273 PO Box 70 2280 AB RIJSWIJK the Netherlands

Tel. +31.70 414 44 00 Fax +31.70 414 44 20 www.1kiwa.com

© 2012 Kiwa Nederland B.V.

All rights reserved. No part of this book may be reproduced, stored in a database or retrieval system, or published, in any form or in any way, electronically, mechanically, by print, photoprint, microfilm or any other means without prior written permission from the publisher.

The use of this evaluation guideline by third parties, for any purpose whatsoever, is only allowed after a written agreement is made with Kiwa to this end.

Validation

This evaluation guideline has been validated by Kiwa on 1 February 2012.

Contents

1	Introduction	1
1.1	General	1
1.2	Field of application / scope	1
1.3	Acceptance of test reports provided by the supplier	1
1.4	Quality declaration	1
2	Terms and definitions	2
3	Procedure for granting the quality declaration	3
3.1	Pre certification tests	3
3.2	Granting the quality declaration	3
4	Requirements and test methods	4
4.1	General	4
4.2	Product requirements	4
4.3	Further specifications materials	4
4.4	Additional specifications	4
5	Marking	6
5.1	General	6
5.2	Low water consumption indication and marking	6
6	Test methods	7
6.1	Determination of the adherence and the durability of plastic coatings	7
6.2	Determination of the minimum flow rate	7
7	Requirements in respect of the quality system	8
7.1	Manager of the quality system	8
7.2	Internal quality control/quality plan	8
7.3	Procedures and working instructions	8
8	Summary of tests and inspections	9
8.1	Test matrix	9
8.2	Inspection of the quality system	9
8.2 9	Inspection of the quality system Agreements on the implementation of certification	
		9
9	Agreements on the implementation of certification	9 10
9 9.1	Agreements on the implementation of certification General	9 10 10
9 9.1 9.2	Agreements on the implementation of certification General Certification staff	9 10 10 10
9 9.1 9.2 9.3	Agreements on the implementation of certification General Certification staff Report Pre certification tests	9 10 10 10 11

Contents

9.7	Interpretation of requirements	11
10	Titles of standards	12
I	Model certificate	13
II	Model IQC-scheme	14

1 Introduction

1.1 General

This evaluation guideline includes all relevant requirements which are adhered to by Kiwa as the basis for the issue and maintenance of a certificate for shower heads and hand showers for sanitary tapware.

This Evaluation Guideline replaces Evaluation Guideline BRL-K658/07 "Shower heads and hand showers for sanitary tapware", dated 16 August 2002.

For the performance of its certification work, Kiwa is bound to the requirements as included in the clause 4.6 "conditions and procedures for granting, maintaining, extending, suspending and withdrawing certification" of EN45011.

1.2 Field of application / scope

The shower heads and hand showers may be used in tap water installations with a maximum working pressure of 1000 kPa. The recommended limits for correct operation are a dynamic pressure between 100 kPa and 500 kPa and a water temperature of maximum 65 °C. Occasional use with water temperatures up to 95°C are permitted if limited to 1 hour maximum. Using the products in water installations with a continuous temperature higher than 65°C is possible. However, this may influence the durability of some parts.

1.3 Acceptance of test reports provided by the supplier

When by the manufacturer reports from test Institutions or laboratories are produced in order to demonstrate that the product meets the requirements of this evaluation guideline, the institute or laboratory shall meet one of the applicable accreditation norms, being;

- NEN-EN-ISO/IEC 17025 for laboratories;
- NEN-EN-ISO/IEC 17020 for inspection bodies;
- NEN-EN 45011 for certification bodies certifying products;

This requirement is being considered to be fulfilled when a certificate of accreditation can be shown, either issued by the Board of Accreditation (RvA) or one of the institutions with which the RvA an agreement of mutual acceptance has been concluded.

The accreditation shall refer to the examination as required in this BRL. When no certificate of accreditation can be shown, Kiwa will verify whether the accreditation norm is fulfilled.

1.4 Quality declaration

The quality declarations to be issued by Kiwa are described as Kiwa product certificate. A model of the certificate to be issued on the basis of this Evaluation Guideline has been included as an Annex.

2 Terms and definitions

In this evaluation guideline the following terms and definitions are applicable:

Evaluation Guideline: the agreements made within the Board of Experts on the subject of certification.

Board of Experts: The Board of Experts "CWK".

Supplier: the party that is responsible for ensuring that the products meet and continue to meet the requirements on which the certification is based.

IQC scheme: a description of the quality inspections carried out by the supplier as part of his quality system.

Product requirements: requirements made specific by means of measures or figures, focusing on (identifiable) characteristics of products and containing a limiting value to be achieved, which limiting value can be calculated or measured in an unequivocal manner.

Pre-certification tests: tests in order to ascertain that all the requirements recorded in the Evaluation Guideline are met.

Inspection tests: tests carried out after the certificate has been granted in order to ascertain whether the certified products continue to meet the requirements recorded in the Evaluation Guideline.

Remark

The test matrix contains a summary showing what tests Kiwa will carry out in the pre-certification stage and in the event of inspections as well as showing the frequency with which the inspection tests will be carried out.

Product certificate: a document, in which Kiwa declares that a product may, on delivery, be deemed to comply with the product specification recorded in the product certificate.

Tap water (origin Drinking Water Directive): water intended for drinking, cooking, food preparation or other domestic purposes.

Remark

- tap water can be drinkingwater or heated drinking water.
- the definition for tap water deflects from that of the Waterleidingwet (Drinking Water Directive).

Working pressure: the highest pressure occurring in the drinking water appliance or in the parts of it, under normal circumstances.

3 Procedure for granting the quality declaration

3.1 Pre certification tests

The pre certification-tests to be performed are based on the (product) requirements as included in this evaluation guideline including the test methods and contain, de pending on the nature of the product to be certified:

- type testing to determine whether the products comply with the product and/or functional requirements,
- Production Process Assessment,
- Assessment of the quality system and the IQC-scheme,
- Assessment on the presence and functioning of the remaining procedure.

3.2 Granting the quality declaration

After finishing the pre-certification tests the results are presented to the person deciding on granting of certificate. This person evaluates the results and decides whether the certificate can be granted or additional data and/or tests are necessary.

4 Requirements and test methods

4.1 General

This chapter contains the requirements the thermostatic mixing valves have to comply with. These requirements will make part of the technical specification of the products, as included in the certificate.

4.2 Product requirements

The requirements the product shall meet and the respective test methods have been laid down in the following standard:

EN 1112 Sanitary tapware - Shower outlets for sanitary tapware for water supply systems of type 1 and type 2 - General technical specifications - March 2008.

4.3 Further specifications materials

4.3.1 Requirements to avoid deterioration of the quality of the drinking water

Products and materials, which (may) come into contact with drinking water or warm tap water, shall not release substances in quantities which can be harmful to the health of the consumer or negatively affect the quality of the drinking water. Therefore, the products or materials shall meet the toxicological, microbiological and organoleptic requirements as laid down in the valid "Ministerial Regulation materials and chemicals drinking water and warm tap water supply" (published in the Government Gazette). Consequently the procedure for obtaining a recognised quality declaration, as specified in the valid Regulation, has to be concluded with positive results.

Products and materials with a quality declaration*, e.g. issued by a foreign certification institute, are allowed to be used in the Netherlands, provided that the Minister has declared this quality declaration equivalent to the quality declaration as meant in the Regulation.

4.3.2 Chemical and mechanical requirements

4.3.2.1 Corrosion resistance

The materials shall be corrosion resistant or protected against corrosion. The materials used may not have an adverse effect on each other.

4.3.2.2 Plasic coatings

After a test according to 6.1 the coating shall comply with;

- EN 248, article 7.1.1. in relation to the corrosion resistance;
- ISO 2409, table 1, class 0 or 1, for the adhesion.
- a. Metallic protection layers

Metallic anticorrosive protection layers shall fulfil the requirements of EN 248.

4.4 Additional specifications

In addition to what has been mentioned in the EN 1112 the following is applicable.

^{*} A quality declaration issued by an independent certification institute in another member state of the European Community than the Netherlands or another state party to the agreement to the European Economic Area, is equivalent to a recognised quality declaration, to the extent that, to the judgment of the Minister of the first mentioned quality declaration, is fulfilled the at least equivalent requirements as meant in the Regulation materials and chemicals drinking water- and warm tap water supply.

4.4.1 Flow rate limiters

Shower heads and hand showers that are furnished with a flow rate limiter shall;

• The flow restrictor shall be mounted in the hand shower or shower head.

• In the documentation shall be stated that removing the flow restrictor has a negative influence on the flow rate and that after removal, the product will probably not comply with the requirements for "Low water consumption".

4.4.2 Minimum flow rate

Shower heads and hand showers shall, within the recommended limits for correct operation, have a minimum flow rate of at least 4.0 l/min. This shall be measured according to 6.2.

Remark

Shower heads and hand showers with a low flow rate may cause problems with the hot water supply devices.

5 Marking

5.1 General

After concluding a Kiwa certification agreement the certified products shall, beside the marks indicated in EN1112, be indelible marked with the certification mark **KIWA ♥**.

The packaging may be provided with the following mark.



5.2 Low water consumption indication and marking

Shower heads and hand showers complying with evaluation guideline BRL-K658, having a minimum flow rate measured according to EN1112:2008 clause 11 between 4.0 l/min and 7.2 l/min, may be furnished with the Kiwa "Low water consumption" mark.

The "Low water consumption" label may be applied to the package.



6 Test methods

6.1 Determination of the adherence and the durability of plastic coatings

6.1.1 Test installation and appliances

For the determination of the adherence and the durability of the plastic coating, first the test pieces have to be conditioned in a bath of which the water is automatically maintained at the temperature required. The appliances used for the determination of the adherence are to be according to ISO 2409.

6.1.2 Test piece

At least two mixer bodies or two control elements, but the number of test pieces must be such that the surface to be tested is at least 10 000 mm².

6.1.3 Test requirements

- During the conditioning of the test pieces:
- the water in the bath shall be 90 ± 3 °C;
- the ambient temperature shall be 20 ± 10 °C.

6.1.4 Procedure

- a. Put the test pieces in the water bath for 1 hour.
- b. Cool the test pieces down to ambient temperature;
- c. Determine the adherence of one test piece according to ISO 2409;
- d. Of the remaining test pieces it is to be deter-mined whether they comply with EN 248.

6.2 Determination of the minimum flow rate

6.2.1 Test installation and appliances

Place the shower head or hand shower into a test installation (type 1) in accordance with EN1112:2008, clause 11.

6.2.2 Test piece

For the test a shower head or hand shower which not has been tested on durability aspects shall be used.

6.2.3 Procedure

- a. Increase the water pressure within 3 seconds from 0 kPa, to a dynamic pressure of 100 ± 10 kPa.
- b. After a stabilization period of at least 10 seconds, measure the flow rate
- c. Repeat a. to c. for all flow positions.

7 Requirements in respect of the quality system

This chapter contains the requirements which have to be met by the supplier's quality system.

7.1 Manager of the quality system

Within the supplier's organizational structure an employee must have been appointed who is in charge of managing the supplier's quality system.

7.2 Internal quality control/quality plan

The supplier shall have an internal quality control scheme (IQC scheme) which is applied by him.

The following must have been demonstrably recorded in this IQC scheme:

- what aspects are checked by the producer;
- according to what methods such inspections are carried out;
- how often these inspections are carried out;
- in what way the inspection results are recorded and kept.

This IQC scheme should at least be an equivalent derivative of the model IQC scheme included in the addendum.

7.3 Procedures and working instructions

The supplier shall be able to submit the following:

- procedures for:
 - o dealing with products showing deviations;
 - o corrective actions to be taken if non-conformities are found;
 - o dealing with complaints about products and/or services delivered;
- the working instructions and inspection forms used.

8 Summary of tests and inspections

This chapter contains a summary of the following tests and inspections to be carried out in the event of certification:

- Pre-certification tests;
- Inspection test as to toxicological requirements and product requirements;
- Inspection of the quality system.

The frequency with which Kiwa will carry out inspection tests is also stated in the summary.

8.1 Test matrix

Description of requirement	Article	Tests within the scope of			
	BRL-K658 or EN1112	Pre- certification		n by Kiwa after of certificate ¹⁾	
			inspection ²⁾	frequency /year	
Materials	BRL-K658				
 Requirements to avoid deterioration of the quality of the drinking water 	4.3.1	Х	Х	2	
Chemical and mechanical requirements	4.3.2	Х	Х	2	
Design requirements	EN 1112				
 Marking and identification 	6	Х	Х	2	
Dimensions	8	Х	Х	2	
Functional requirements	EN 1112				
Watertightness	9	Х	Х	2	
Mechanical strength	10.2	Х	Х	2	
Thermal shock	10.3	Х	Х	2	
• Flow rate	11	Х	Х	2	
Acoustic properties	12	Х	Х		
Rotary connection	14	Х			
Additional product requirements	BRL-K658				
• Flow rate limiters	4.4.1	Х	Х	2	
Minimum flow rate	4.4.2	Х	Х	2	
Marking	BRL-K658				
Certification mark	5.1	Х	Х	2	
Low water consumption	Error! Referenc e source not found.	Х	Х	2	

¹⁾ In case of significant changes of the product or production process, compliance of the product to the performance requirements shall be determined

²⁾ Inspections as indicated are to be conducted by the inspector or by the manufacturer, whether or not in presence of the inspector.

8.2 Inspection of the quality system

The quality system will be checked by Kiwa on the basis of the IQC scheme. The inspection contains at least those aspects mentioned in the Kiwa Regulations for Product certification.

9 Agreements on the implementation of certification

9.1 General

Beside the requirements included in these evaluation guidelines, also the general rules for certification as included in the Kiwa Regulations for Product Certification apply.

These rules are in particular

- The general rules for conducting the pre-certification tests, to be distinguished in:

 the way suppliers are to be informed about an application is being handled,
 how the test are conducted,
 - o the decision to be taken as a result of the pre certification tests.
- The general directions for conducting inspections and the aspects to be audited,
- The measurements to be taken by Kiwa in case of Non Conformities,
- Measurements taken by Kiwa in case of improper Use of Certificates, Certification Marks, Pictograms and Logos,
- Terms for termination of the certificate,
- The possibility to lodge an appeal against decisions of measurements taken by Kiwa.

9.2 Certification staff

The staff involved in the certification may be sub-divided into:

- certification experts: they are in charge of carrying out the pre-certification tests and assessing the inspectors' reports;
- inspectors: they are in charge of carrying out external inspections at the supplier's works;
- decision-makers: they are in charge of taking decisions in connection with the pre-certification tests carried out, continuing the certification in connection with the inspections carried out and taking decisions on the need to take corrective actions.

9.2.1 Qualification requirements

The following qualification requirements have been set by the Board of Experts for the subject matter of this Evaluation Guideline:

EN45011	Certification Expert	Inspector	Decision maker
Education - general	 Technical higher-level	 Intermediate-level	 Higher level
	professional education Internal training	professional education Internal training	professional education Internal training
	certification and Kiwa	certification and Kiwa	certification and Kiwa
	policy Training auditing	policy Training auditing	policy Training auditing
Education - specific	 for BRL relevant	 for BRL relevant	 not applicable unless
	technical education specific studies and	technical education specific studies and	specific requirements
	training (know-how	training (know-how	have been specified by
	and skills)	and skills)	the BoE
Experience - general	• 1 year of relevant work experience with at least 4 pre certification tests of which one carried out independent under supervision.	• 1 year of relevant work experience with at least 4 inspections of which one carried out independent under supervision	• 4 year of relevant work experience with at least 1 year in certification

EN45011	Certification Expert	Inspector	Decision maker
Experience - specific	• Detailed knowledge of the BRL and 4 certification tests carried out on the basis of the BRL or one related.	• Detailed knowledge of the BRL and 4 inspections carried out on the basis of the BRL or one related.	• general knowledge of the BRL

The level of education and the experience of the certification staff involved should be demonstrably recorded.

9.2.2 Qualification

The qualification of the Certification staff shall be demonstrated by means of assessing the education and experience to the requirements mentioned before. In case staff is to be qualified on the basis of deflecting criteria, written records shall be kept.

The authority to qualify staff is dedicated to:

- decision makers: qualification of certification experts and inspectors,
- Management of Kiwa: qualification of decision makers.

9.3 Report Pre certification tests

Kiwa records the results of the pre certification tests in a report. This report shall comply with the following requirements:

- completeness: the reports verdicts about all requirements included in the evaluation guideline,
- traceability: the findings on which the verdicts have been based shall be recorded traceable,
- basis for decision: the decision maker shall be able to base his decision on the findings included in the report.

9.4 Decision for granting the certificate

The decision for granting the certificate shall be made by a qualified decision maker which has not been involved in the pre certification tests. The decision shall be recorded traceable.

9.5 Lay out of quality declaration

The product certificate shall be conform the model included as an annex

9.6 Nature and frequency of external inspections

The certification body shall carry out Audits at the supplier at regular intervals to check whether the supplier complies with his obligations. About the frequency of inspections the Board of Experts decides. At the time this Evaluation Guideline took effect, the frequency was set at number of 2 inspection visits per year.

Inspections shall at least refer to:

- The suppliers IQC-scheme and the results obtained from inspections carried out by the supplier,
- The correct way of marking of certified products
- Complying with required procedures.

The results of each inspection shall be traceable recorded in a report.


9.7 Interpretation of requirements

The Board of Experts may record the interpretation of requirements of these evaluation guidelines in one separate interpretation document.

10 Titles of standards

Number	Title
NEN 1006	Algemene voorschriften voor leidingwater installaties
NEN-EN 1112	Sanitary tapware - Shower outlets for sanitary tapware for water supply systems of type 1 and type 2 - General technical specification", March 2008
EN 248	Sanitary tapware. General technical specifications for electrodeposited nickel chrome coatings
ISO 2409	Paint and varnishes, Cross-cut test

I Model certificate



II Model IQC-scheme

Subjects	Aspects	Method	Frequency	Registration
 Raw materials or materials supplied: Recipe sheets Incoming inspection raw materials 				
Production process, production equipment, materials: • procedures • work instructions • equipment • release of product				
Finished-products test procedures instructions equipment registration identification/marking 				
Measuring and testing equipment • measuring equipment • calibration				
Logistics • internal transport • storage • preservation • packaging				